



SourceTechnologies®

ST9715

- Small footprint
- Performance & security
- Entry-level pricing



SECURE MICR PRINTERS

| | | |
|--------------------------------------|---|--|
| Model No. | ST9715 | |
| Print Speed (pages/min.) | Up to 35 ppm | |
| Time to First Page | As fast as 6.5 seconds | |
| Maximum Duty Cycle (pgs./mo.) | Up to 50,000 | |
| Recommended Volume (pgs./mo.) | 500 - 2,500 | |
| Maximum Resolution | 1,200 x 1,200 dpi | |
| Processor | Dual Core, 800 MHz | |
| Memory (Standard/Max) | 128MB / 128MB | |
| Standard Connectivity | USB 2.0 (Type B), 10/100 Ethernet, Parallel | |
| Optional Connectivity | Wireless | |
| Duplex Printing | Integrated | |
| Paper Capacity* | | |
| Standard (in/out) | 250/150 | |
| Maximum (in/out) | 850/150 | |
| Paper Sources | | |
| Standard (in/out) | 2/1 | |
| Maximum (in/out) | 3/1 | |
| Emulations | PS3, PCL 5e, PCL6, Microsoft XPS | |
| Operator's Panel | 2 Line Monochrome LCD | |
| MICR Cartridge Yields* | Starter: 1.5k Replacement: 5k | |
| Imaging Unit** | Up to 40,000 | |
| Dimensions | 10.3 x 15.7 x 15.0 | |
| Weight (lbs.) | 30.9 | |
| Warranty | 1-year, return-to-depot from date of sale | |
| Quality Assurance Features | MICR Guarantee to ANSI / ABA Standards Auto Density Control MICR Toner Detection Low Toner Warning and Auto Stop | Optimized Fusing & Transfer Voltage Originally Manufactured MICR Toner Regulated Fuser Temperature |
| Secure Fonts | E-13B MICR Font CMC7 MICR Font Microprint Font | Secure Numeric Font ICR Numeric Font |
| Security Features | Set Copies to one (1) Auto Jam Recovery Disable | Password Protection Optional: Physical Drawer Lock |
| Options | 550 Sheet Tray | |

*20lb or 75 GSM Paper. Maximum input amount shown is the maximum capacity that can be used for non-MICR printing; high-capacity input trays may interfere with printing quality MICR documents. The maximum input capacity for MICR printing may be lower than the values shown.

1Average standard page yield value declared in accordance with ISO/IEC 19752.

2Maximum Yield estimate based on 3 average letter/A4-size pages per print job at approximately 5% coverage. Actual yield may vary.

All specifications are subject to change without notice.



| MICR Feature | Description | Benefit |
|--|---|--|
| E13B Font | Widely accepted MICR font used in printing MICR encoded documents in the US, Canada, Mexico, the Far-East and some other countries | Meets ASC X9B/US specification for MICR font and necessary to process checks through the system |
| CMC7 Font | Alternative MICR font used to print MICR encoded documents in many European and most Latin American countries. Numeric character set only | Meets international standards (ISO) 1004. |
| Secure Numeric Font | Unique ST-designed font that is very difficult to alter because of a special background and very small text & numeric print embedded in the amount line of the check. | Additional layer of security at the document level. Minimizes the risk of fraud. |
| Microprint Font | Extremely small type font allows one to embed micro text and numbers inside lines of print on the MICR document. Denoted by the letters "MP" | Additional layer of security at the document level. Minimizes the risk of fraud. |
| ICR Numeric Font | Image readable secure font designed to be read by imaging equipment utilized by many financial institutions. | Additional layer of security at the document level. Minimizes the risk of fraud. |
| Set Copies to one (1) | A PCL setting that tells the printer to print the job only once. | Prevents fraud by disallowing the printing of multiple copies of a document. |
| Auto Jam Recovery Disable | Automatically turns Jam Recovery OFF when checks are being printed | Prevents multiple copies of a check from being printed |
| Password Protection | Prevents access to check-printing resources (stored signatures, MICR fonts, form overlays) without the proper password | Prevents unauthorized access to MICR and Secure fonts, and user-specific signatures and form overlays |
| MICR Toner Detection | Detects whether MICR toner or regular toner is installed in the printer | Prevents printing of MICR documents with regular toner- preventing costly bank rejects |
| Toner Low Warnings | Printer alerts user when MICR toner is low | Ensures quality MICR printing |
| 3 Year MICR Guarantee to ANSI/ABA Standards | Source Technologies ensures the readability performance of our MICR printers | Ensures the quality of printed negotiable documents |
| Auto Density Control for Toner | Ensures conformance to signal strength standards throughout cartridge life | Ensures conformance and bank acceptance |
| Originally Manufactured MICR Toner Cartridge | Toner cartridges are built and tested using MICR toner | No "refilled" or "remanufactured" cartridges to introduce potential problems that would damage the printer |
| Regulated Fuser Temperature for Optimum Performance | Fusing temperature controlled to match MICR toner and check stock paper weights | Maximizes toner adherence. Less exposure to fraud due to less toner lift off |
| Tray Locking | Key lock on printer and expansion drawers | Prevents fraud by keeping check stock safe and prevents check paper waste |