



SourceTechnologies®

Accel 7450S

- Handles up to 7-Part Forms
- Print speeds to 528 cps
- 24 Pin Printhead
- Ideal for Finance & Insurance Applications



Printer Model	Accel 7450S
Print Head	24 pins and 0.010 inches (diameter of wire)
Resolution	360 x 360 dpi (Max.)
Character Set	ASCII: 17 international character sets
Interfaces	USB interface: 2.0 Full-Speed, RS-232C Serial interface (DB 9-PIN), Optional Ethernet interface (10/100 Base-T)
Input Buffer	132 KB
Control Panel	8 Buttons + 4 LED indicators + LCD
Printing width	136 columns (10 CPI) / 13.6 inches
Paper Feed Type	Cut sheet: Load/eject from front; Load from front and eject from rear Tractor paper: Load from rear, eject from front
Continuous Paper	Width: 5 in ~ 15.98 in
Cut sheet / Card	Width: 5 in ~ 16.93 in / Length: 5 in ~ 6.93 in
Thickness Adjust	Automatically detect the paper thickness and adjust the gap, or adjust through gap adjust lever.
Copies	Up to 7-part forms , 0.020" Max Thickness
Paper Handling	Paper thickness detect, Skew detect, Paper edge detect
Special Functions	LCD, Pin Break compensation, Pin Switch, Automatic Emulation Match
Noise	<58 dB (A) (ISO7779 standard)
Character Pitch	ASCII: 10 CPI, 12 CPI, 15 CPI, 17 CPI, 20 CPI, proportional
Line Space	1/3 inch, 1/4 inch, 1/6 inch, 1/8 inch, 1/9 inch and n/360 inch
Paper Feeding Speed (Max)	6 inches per second (continuous feed)
Printing Direction	Bi-directional logic seeking
Ribbon Life	20 million characters (draft mode)
Emulations	EPSON ESC/PK2, OKI 5530SC, IBM 2391
Code Page	U.S.A, MULTI, PORTUGAL, CANADA, NORWAY, EAST EURO, CYRILLIC, RUSSIAN, HUNGARY, KAMENICKY, TURKEY, ICELAND, BULGARIA, MAZOVIA, GRK 437, GRK 851, GRK8859-7, GRK 1253, ARAB NLS, ARAB EXT, WIN LAT1, WIN LAT2, ISL LTN1, ISO LTN2, TUR8859-9, ISO LTN9, KBL, LATIN 7
Fonts	ASCII: Draft, Roman, Sans Serif, Courier, Prestige, Script, OCR-B, OCR-A, Orator <i>Note: In high speed mode or super high mode, printer would automatically change the ASCII font to Draft when printing ASCII characters.</i>
Bar Codes	EAN-13, EAN-8, Interleaved 2 of 5, Matrix 2 of 5, Industrial 2 of 5, Code 39, Code 128 B, Code 128 C, NW-7
Physical Dimensions	25 in (width) x 13.19 in (depth) x 11.57 in (height) (no tractor and paper rack) 25 in (width) x 18.31 in (depth) x 11.57 in (height) (with tractor and paper rack)
Weight	~48.5 lbs
Power Supply	Input Voltage: 120 V (AC); Frequency: 60Hz
Warranty	1 year

Speed (ASCII)		
Speed	10 CPI	12 CPI
High Density	180 CPS	216 CPS
Normal Speed	240 CPS	288 CPS
High 1	360 CPS	432 CPS
High 2	440 CPS	528 CPS